

Equipped with additional tools, a Brokk becomes even more profitable for your business. Grapples, scabblers, buckets, drills and other devices greatly expand the machine's efficiency and versatility. Here's our wide and ever-expanding range of original Brokk attachments:



SB302



■ BREAKERS

	Hitting power*	Blows/min	Weight	Made for
SB 52	101 J/Nm	720 – 1,680	60 kg/132 lbs	Brokk 60
SB 152	254 J/Nm	780 – 1,920	142 kg/315 lbs	Brokk 100, 160
SB 202	406 J/Nm	840 – 1,800	212 kg/470 lbs	Brokk 160
SB 302	610 J/Nm	600 – 1,410	310 kg/685 lbs	Brokk 260
SB 452	855 J/Nm	540 – 1,260	450 kg/990 lbs	Brokk 400
SB 552	1,048 J/Nm	660 – 1,140	535 kg/1,177 lbs	Brokk 400
MB 1200	2,709 J/Nm	340 – 680	1,495 kg/3,296 lbs	Brokk 800

*Actual output, impact energy class (Joule/Nm)

A variety of chisels and tools can be fitted to the breakers. Other breaker brands can also be used on Brokk machines. Contact your local Brokk dealer or Brokk AB for information.



PTA-09



■ SIDE ANGLING DEVICE

	Angle	Weight*	Made for
PTA-04,5	±60°	140 kg/309 lbs	SB 102/Brokk 100
PTA-06	±70°	215 kg/474 lbs	SB 152/Brokk 160
PTA-07	±70°	330 kg/728 lbs	SB 202/Brokk 260
PTA-09	±55°	555 kg/1,224 lbs	SB 302/Brokk 400

*With breaker



CONCRETE CRUSHERS**



CC520

	Jaw opening	Rebars	Crushing force	Weight	Made for
CC260	260 mm/10 in	Ø20 mm/0.8 in	220 kN/22 t/ 50 Klb	75 kg/ 165 lbs	Brokk 60
CC340	343 mm/14 in	Ø28 mm/1.1 in	360 kN /36.7 t/ 81 Klb	160 kg/ 353 lbs	Brokk 100
CC420*	420 mm/16.5 in	Ø28 mm/1.1 in	382 kN/38.2 t/ 85 Klb	265 kg/ 585 lbs	Brokk 160
CC520*	540 mm/21.3 in	Ø28 mm/1.1 in	466 kN/48 t/ 105 Klb	410 kg/ 900 lbs	Brokk 260
CC700*	650 mm/26 in	Ø28 mm/1.1 in	680 kN/69 t/ 162 Klb	595 kg/ 1,310 lbs	Brokk 400, 800

*Option pulverizing pads

**Free rotation



METAL SHEARS*



BMS 250

	Cutting force	Jaw opening	Weight	Made for
HCS6	169 kN/17 t/37 Klb	320 mm/12.6 in	55 kg/120 lbs	Brokk 60, 100
HCS7	312 kN/31 t/69 Klb	350 mm/13.8 in	123 kg/270 lbs	Brokk 100, 160
CC420S	740 kN/75.4 t/166 Klb	145 mm/5.7 in	310 kg/680 lbs	Brokk 160, 260
CC700S	1,772 kN/181 t/398 Klb	271 mm/10.5 in	690 kg/1520 lbs	Brokk 400, 800
BMS 100	1,020 kN/102 t/225 Klb	185 mm/7.3 in	385 kg/850 lbs	Brokk 160, 260
BMS 140	1,380 kN/138 t/304 Klb	245 mm/9.6 in	645 kg/1,420 lbs	Brokk 400
BMS 250	2,500 kN/250 t/550 Klb	395 mm/15.5 in	1,205 kg/2,650 lbs	Brokk 800

*Requires one extra hydraulic function
Rotator with continuous rotation



BUCKETS*



250 l

Volume	Width	Weight	Made for
20 l/0.7 cu ft	330 mm/12 in	20 kg/44 lbs	Brokk 60
60 l/2.1 cu ft	520 mm/20 in	61 kg/134 lbs	Brokk 100
80 l/2.8 cu ft	690 mm/27 in	76 kg/167 lbs	Brokk 160
250 l/8.8 cu ft	960 mm/38 in	195 kg/430 lbs	Brokk 260, 400
700 l/25.2 cu ft	945 mm/37.2 in	650 kg/1433 lbs	Brokk 800

*See load diagram for each Brokk machine



CO5HPX




■ CLAMSHELL BUCKETS*

	Volume	Opening range	Width	Weight	Made for
CO2H-25	25 l/0.9 cu ft	667 mm/26 in	250 mm/10 in	110 kg/240 lbs	Brokk 100
CO3H-35	65 l/2.3 cu ft	879 mm/35 in	350 mm/14 in	175 kg/385 lbs	Brokk 160
CO5H-40	115 l/4.1 cu ft	1,090 mm/43 in	400 mm/16 in	210 kg/460 lbs	Brokk 260
CO5HPX-60	170 l/6.1 cu ft	1,110 mm/44 in	600 mm/24 in	375 kg/825 lbs	Brokk 400
CO8HPX-80	300 l/10.6 cu ft	1,250 mm/50 in	800 mm/31 in	580 kg/1,275 lbs	Brokk 800

*See load diagram for each Brokk machine
Rotator with continuous rotation
Requires one extra hydraulic function



AO5H-40



■ MULTI PURPOSE GRAPPLES*

	Volume	Opening range	Width	Weight	Made for
AO2H-30	35 l/1.2 cu ft	760 mm/30 in	300 mm/12 in	133 kg/295 lbs	Brokk 100, 160
AO3H-40	70 l/2.5 cu ft	1,474 mm/58 in	390 mm/15 in	265 kg/585 lbs	Brokk 260
AO5HPX-40	100 l/3.6 cu ft	1,399 mm/55 in	400 mm/16 in	375 kg/825 lbs	Brokk 400
AO9HPX-50	200 l/7.1 cu ft	1,695 mm/66 in	500 mm/20 in	675 kg/1,490 lbs	Brokk 800

Orange Peel Grapple

KM651-4 180	180 l/6.4 cu ft	1,450 mm/57 in	1,070 mm/42 in	520 kg/ 1,150 lbs	Brokk 400
KM651-4 250	250 l/8.8 cu ft	1,550 mm/61 in	1,285 mm/51 in	870 kg/ 1,920 lbs	Brokk 800

*See load diagram for each Brokk machine
Requires one extra hydraulic function
Rotator with continuous rotation



KM650

G50



■ SORTING & DEMOLITION GRAPPLES*

	Jaw opening	Weight	Made for
G30	300 mm/12 in	42 kg/92 lbs	Brokk 60
G50	500 mm/20 in	133 kg/295 lbs	Brokk 100, 160
D02H-30	792 mm/31 in	133 kg/295 lbs	Brokk 100, 160
D03HPX-40	975 mm/38 in	310 kg/680 lbs	Brokk 260, 400
D05HPX-50	1,135 mm/45 in	375 kg/825 lbs	Brokk 400
D09HPX-60	1,400 mm/56 in	595 kg/1,310 lbs	Brokk 800

*See load diagram for each Brokk machine
Requires one extra hydraulic function
Rotator with continuous rotation



D02H

ER 100



SCABBLERS

	Cutting depth**	Width	Weight	Made for
RT 15*	0-5 mm/0-0.2 in	203 mm/8 in	82 kg/180 lbs	Brokk 60, 100, 160
ER 50	0-30 mm/0-1.2 in	480 mm/19 in	115 kg/250 lbs	Brokk 100, 160
ER 100	0-65 mm/0-2.6 in	610 mm/24 in	300 kg/660 lbs	Brokk 160, 260, 400
ER 250	0-80 mm/0-3.2 in	680 mm/26 in	520 kg/1,150 lbs	Brokk 400***

*Cover and suction on request

**Data depending on concrete quality

***B800 on request depending on requirement

BCP250



PLANERS

	Cutting depth	Width	Weight	Made for
BCP 215* ***	0-6 mm/0-0.25 in	215 mm/8.5 in	220 kg/485 lbs	Brokk 100
BCP 250* ***	0-6 mm/0-0.25 in	265 mm/10.4 in	250 kg/551 lbs	Brokk 160
BCP 350* ***	0-6 mm/0-0.25 in	335 mm/13.2 in	310 kg/683 lbs	Brokk 260, 400
PLB 300* **	0-50 mm/0-2 in	300 mm/11.8 in	390 kg/860 lbs	Brokk 260, 400

*Available with cover and suction

**Other models on request

***Requires extra hydraulic function, drainage hose, cable kit, counter weight in some occasions
Requires load holding.
On request

PLB 300



TE 160-100



DRILLING EQUIPMENT


	Length	Bore depth	Drill diam. (Std)**	Water or airflushing	Weight	Made for
TE 160-100	1,900 mm/ 75 in	1,000 mm/39 in	25-50 mm/ 1-2 in	0.5 m³/min at 5-20 bar or 25 l/min at 4-20 bar	140 kg/ 308 lbs	Brokk 100
TE 260-180*** (concrete and rock)	2,900 mm/ 115 in	1,800 mm/63 in* max 10 m/395 in	33-76 mm/ 1.3 - 3 in	0.5 m³/min at 5-20 bar or 25 l/min at 4-20 bar	415 kg/ 915 lbs	Brokk 160, 260, 400
TE 260-240*** (concrete and rock)	3,500 mm/ 138 in	2,400 mm/87 in* max 10 m/395 in	33-76 mm/ 1.3 - 3 in	0.5 m³/min at 5-20 bar or 25 l/min at 4-20 bar	432 kg/ 952 lbs	Brokk 260, 400
TE 350-240*** (concrete and rock)	3,590 mm/ 141 in	2,400 mm/87 in* max 20 m/790 in	41-102 mm/ 1.6 - 4 in	0.5 m³/min at 5-20 bar or 25 l/min at 4-20 bar	760 kg/ 1675 lbs	Brokk 400, 800

*Per stroke with open centerlizer

**Additional drill diameter on request

***Requires drainage hose, cable kit, counter weight in some occasions

Brokk Beam
Grapple



TUNNEL AND MINING EQUIPMENT

	Jaw opening	Beam weight*	Weight	Made for
Brokk Beam Grapple***	240 mm/9.5 in	500 kg/1,100 lb	320 kg/705 lbs	Brokk 260, 400, 800



Brokk Shot
Crete

	Concrete hose (di)	Gunning pressure	Air pressure	Weight	Made for
Brokk Shot Crete**	45 mm/ 1.77 in	65 bar/ 6.5 mpa	0.1-0.2 m³/min at 3-5 bar	180 kg/400 lbs	Brokk 260, 400, 800

*See load diagram for each Brokk machine

**Requires two extra hydraulic functions

***Requires drop-check valves

Cut Off Saw



CUT OFF SAW*

	Saw disk diameter**	Cutting depth***	Weight****	Made for
BCS 8	400 mm/15.75 in	170 mm/6.7 in	70 kg/155 lbs	Brokk 60
BCS10	400 mm/15.75 in	170 mm/6.7 in	85 kg/190 lbs	Brokk 100, 160
BCS 25 *****	800 mm/31.5 in	260 mm/10.2 in	250 kg/550 lbs	Brokk 160, 260
BCS 35 *****	800 mm/31.5 in	260 mm/10.2 in	260 kg/575 lbs	Brokk 260, 400, 800

*Requires one extra hydraulic function

**Different saw disks available depending on material

***With new saw disk

****Depending on machine model

*****Requires drainage hose